

DROP HEADS THREADERS


EGA Master drop heads threaders are specially manufactured for precise operation due to **the internal machining of the aluminum cover**, the which makes the four combs perfectly concentric and thus achieve good thread quality.



1. They allow to carry out threads easily and High quality of manually.



2. The neck is longer, favoring a better positioning, reducing vibrations, that improve the thread quality and facilitating the extraction of the head of the ratchet.



3. They include **different head sizes** to suit all needs.

4. Games available for **BSPT and NPT threads**.

TECHNICAL CHARACTERISTICS

MATERIAL	HEADS	BODY: Malleable cast iron
		LID: Aluminum
		COMBS: Special steel
	RATTLE	Aluminum alloy
HARDNESS	REDUCER	Aluminum
	COMBS	58-62 HRc
	RATTLE	45-50 HRc
FINISH	HEADS	Painted in semi-textured black epoxy powder
	RATTLE	Painted in semi-textured epoxy powder in Red RAL-2002

INTERCHANGEABLE HEAD DIE



COD.		 O.D. inch	 Kg			
63020	BSPT	1/4-1.1/4	7,5	59018, 59019, 63003, 63004, 63005, 63006	63000	51000
63021		3/8-1.1/4	7,0	59019, 63003, 63004, 63005, 63006		
63022		1/2-1.1/4	6,5	63003, 63004, 63005, 63006		
63023		1/4-1		59018, 59019, 63003, 63004, 63005		
63024		3/8-1		59019, 63003, 63004, 63005		
63025		1/2-1	5,5	63003, 63004, 63005		

COD.		 O.D. inch	 Kg			
63026	NPT	1/4-1.1/4	7,5	63011, 63012, 63013, 63014, 63015, 63016	63000	51000
63027		3/8-1.1/4	7,0	63012, 63013, 63014, 63015, 63016		
63028		1/2-1.1/4	6,5	63013, 63014, 63015, 63016		
63029		1/4-1		63011, 63012, 63013, 63014, 63015		
63030		3/8-1		63012, 63013, 63014, 63015		
63031		1/2-1	5,5	63013, 63014, 63015		



COD.		 O.D. inch	 Kg			
63036	BSPT	1.1/4-2	9,8	63007, 63008, 63009	63010	50002
63037		1.1/2-2	8,4	63008, 63009		

COD.		 O.D. inch	 Kg			
63038	NPT	1.1/4-2	9,8	63017, 63018, 63019	63010	50002
63039		1.1/2-2	8,4	63018, 63019		



COD.		 O.D. inch	 Kg			
63134	BSPT	1/4-2	14	59018, 59019, 63003, 63004, 63005, 63006, 63008, 63009	63010	50002
63133		3/8-2		59019, 63003, 63004, 63005, 63006, 63008, 63009		
63132		1/2-2		63003, 63004, 63005, 63006, 63008, 63009		

COD.		 O.D. inch	 Kg			
63139	NPT	1/4-2	14	63011, 63012, 63013, 63014, 63015, 63016, 63018, 63019	63010	50002
63138		3/8-2		63012, 63013, 63014, 63015, 63016, 63018, 63019		
63137		1/2-2		63013, 63014, 63015, 63016, 63018, 63019		

HEADS



COD.		 O.D. inch	 Kg		
59018	BSPT	1/4	0,6	1	•
59019		3/8			
63003		1/2			
63004		3/4	0,5		
63005		1	0,8		
63006		1.1/4	0,9		

HEADS



COD.		 O.D. inch	 Kg		
63007	BSPT	1.1/4	1,5	1	-
63008		1.1/2	1,9		
63009		2			

CHARACTERISTICS

Heavy series

COD.		 O.D. inch	 Kg		
63011	NPT	1/4	0,6	1	•
63012		3/8			
63013		1/2			
63014		3/4	0,5		
63015		1	0,8		
63016		1.1/4	0,9		

COD.		 O.D. inch	 Kg		
63017	NPT	1.1/4	1,5	1	-
63018		1.1/2	1,9		
63019		2			

CHARACTERISTICS

Heavy series

DIES



COD.		 O.D. inch	 Kg		
59022	BSPT	1/4	70	1	
59023		3/8			
63042		1/2			
63043		3/4	130		
63044		1			
63045		1.1/4			
63046		1.1/2	230		
63047		2			

COD.		 O.D. inch	 9	
63050	NPT	1/4	70	1
63051		3/8		
63052		1/2		
63053		3/4	130	
63054		1		
63055		1.1/4		
63056		1.1/2	230	
63057		2		

RATCHETS



COD.	O.D. inch	Kg		
63000	1/4-1.1/4	1,5	1	•
63010	1.1/4-2	3,0		

CASE



COD.	L x W x H (mm)
51000	410 x 210 x 95
50002	640 x 340 x 155

REDUCER



COD.	O.D. inch	g	
80833	1/4-1.1/4	15	•

CUTTING OIL



COD.	CAP. (ml)	
64007	100	1

PTFE SEALING TAPE FOR THREADS



COD.	L (m)	W x H (mm)	Density (g/cm3)	g	
51575	10	12 x 0,075	0,20	10	1
51576	15		0,30	15	